AIRLESS SPRAY TIPS

HEA Tips 330-XXX

HEA HIGH EFFICIENCY AIRLESS

FAN PATTERN WIDTH	ORIFICE SIZE (INCHES)							
	INCHES	MM	0.011	0.013	0.015	0.017	0.019	0.021
	4-6	102-152	211	213				
	6-8	152-203	311	313				
	8-10	203-254	411	413	415	417		421
	10-12	254-305			515	517	519	521
	12-14	305-356			615	617	619	621
	Flow (gpm)	----	0.09	0.12	0.18	0.24	0.31	0.47
	Flow (lpm)	----	0.34	0.45	0.68	0.91	1.17	1.79

Maximum Working Pressure: 5000 psi (34.5 MPa)

HEA REVERSIBLE TIP

- Optimized to spray all architectural paints and coatings at 1,000 psi at production speed
- Decreases overspray up to 55% allowing contractors to spray more
- Less pressure equals less stress extending pump life and extending time between repacks
- Two times the life of a standard reversible tip



HEA Tip

TR[1] Tips 695-XXX

FAN PATTERN WIDTH	ORIFICE SIZE (INCHES)										
	INCHES	MM	0.009	0.011	0.013	0.015	0.017	0.019	0.021	0.025	0.027
	2–4	51–102									
	4–6	102–152	209	211	213	215	217				
	6–8	152–203		311	313	315	317				
	8–10	203–254		411	413	415	417				
	10–12	254–305			513	515	517	519	521	525	
	12–14	305–356									627
	Flow (gpm)	---	0.09	0.12	0.18	0.24	0.31	0.39	0.47	0.67	0.78
	Flow (lpm)	---	0.34	0.45	0.68	0.91	1.17	1.47	1.78	2.53	2.95

Maximum Working Pressure: 5000 psi (34.5 MPa)

TR[1] REVERSIBLE TIP

- The best overall performing tip in the industry
- Fan pattern stays wider longer
- An orifice that outlasts competitive tips delivering consistent film thickness and less wasted paint
- Fits all Titan and most other industry spray gun guards

Line Striping Tips 697-XXX

FAN PATTERN WIDTH	ORIFICE SIZE (INCHES)														
	INCHES	MM	0.013	0.015	0.017	0.019	0.021	0.023	0.025	0.027	0.029	0.031	0.035	0.039	0.043
	2	51	213	215	217	219									
	4	102	413	415	417	419	421	423	425	427	429	431	435	439	443
	6	152		615	617	619	621	623	625	627	629	631	635	639	643
	8–10	203–254					821	823	825	827	829	831	835	839	843
	Flow (gpm)	---	0.18	0.24	0.31	0.39	0.47	0.57	0.67	0.78	0.91	1.03	1.32	1.64	1.99
	Flow (lpm)	---	0.68	0.91	1.17	1.47	1.78	2.15	2.53	2.95	3.44	3.89	4.99	6.20	7.52

Maximum Working Pressure: 5000 psi (34.5 MPa)



TR[1] Reversible Tip

High Pressure Tip

Line Striping Tip

High Pressure Tips 696-XXX

FAN PATTERN WIDTH	ORIFICE SIZE (INCHES)															
	INCHES	MM	0.011	0.013	0.015	0.017	0.019	0.021	0.023	0.025	0.027	0.031	0.035	0.037	0.039	0.043
	4–6	102–152	211	213												
	6–8	152–203			315	317	319	321	323	325						
	8–10	203–254			415	417	419									
	10–12	254–305			515	517	519	521	523	525	527	531	535	537		543
	12–14	305–356									627					
	14–16	356–406						721								
	16–18	406–457											835		839	
	18–20	457–508							923							
	Flow (gpm)	---	0.13	0.18	0.24	0.31	0.39	0.47	0.57	0.67	0.78	1.03	1.32	1.40	1.64	1.99
	Flow (lpm)	---	0.45	0.68	0.91	1.17	1.47	1.78	2.15	2.53	2.95	3.89	4.99	5.29	6.20	7.52

Maximum Working Pressure: 7700 psi (53.1 MPa)