

LIQUID RUBBERIZED ASPHALT CRACK SEALER

DESCRIPTION: A filler asphalt emulsion fortified with rubber to produce a liquid mastic sealant.

USES: Sealer for masonry and bituminous paving cracks or any other place where paving faults require a durable elastic seal. Provides a lasting strong resilient adhesive bond to masonry, concrete or asphalt surfaces against seepage of water and other elements.

APPLICATION:

1. Application should be made when the temperature is above 50°F and no rain is expected for 24 hours.
2. Stir well and it will be ready to use. Do not thin.
3. Crack surfaces must be free of grease, oil and other foreign matter. Sweep or blow with compressed air the side surfaces to remove all mud, dirt, dust and other loose debris.
4. Pour into depression to a full bead and then force sealant into the joint or crack with a scraper or putty knife. The easiest method of application is to use a container that has a spout or a caulking gun.
5. After drying, the first application may show shrinkage cracks if the depression is large. Apply another full bead of sealant over the shrinkage.
6. Allow seal to cure for 24 hours before allowing traffic. Tools and spillage can be wiped clean with a cloth dampened with water.

COVERAGE: 300 linear feet per gallon 1/8" x 1/4"

CURING TIME: Approximately 24 hours.

STORAGE: Keep from freezing. Store in heated area during cold weather, maintain forty (40°) F temperature.



www.AsphaltKingdom.com

KEEP OUT OF REACH OF CHILDREN

WARNING

MAY CAUSE SKIN OR EYE IRRITATION. HARMFUL IF SWALLOWED — MAY SENSITIZE SKIN. USE WITH GOOD VENTILATION.

WARRANTY: This product is guaranteed to meet the requirements of our own product specification. However, it is sold, without warranty, expressed or implied as workmanship, weather, quality of other materials and other variable factors affecting results that are beyond our control. We do not assume any risks or liabilities associated with the methods of installation or installations results, beyond replacing any unsatisfactory material of our manufacture not complying with our specification.

PRECAUTIONS AND FIRST AID: Avoid contact with eyes and skin. In case of eye contact, flush eyes with plenty of cold water and call a physician at once! Do NOT take internally. If swallowed, do not induce vomiting. Call a physician at once! Harmful or fatal if swallowed.

SKIN IRRITATION: Avoid contact with skin. Work carefully and avoid spillage on skin or clothing. Remove from skin at once by wiping with waterless hand cleaner followed by soap and water. Get medical attention if irritation persists.

MAY SENSITIZE SKIN: On some persons, this product may cause skin irritation or burns. Use a protective cream or vaseline before applying. Wear protective clothing, including gloves and safety goggles. Close container after each use and protect from freezing.

USE WITH GOOD VENTILATION: Avoid breathing of vapor. In confined areas good forced ventilation must be used. Do not use around food products or where odor may penetrate to cause an odor problem.

COMPOSITION: Neoprene rubber, asphalt and selected mineral filler.