Asphalt Kingdom

SAFETY DATA SHEET

1. Identification

Product identifier Deery Hot Applied Sealants

Other means of identification

Synonyms 101, 101ELT, 101ELTCH, 101KS, 101MI, 102, 102GL,102GL-18B, 102P, 102PL, 103, 103-25,

103-25103GL, 103GLCA, 103GLCH, 103GLWY, 103P, 110, 115, 115AR, 115UT, 180, 180CA, 180NE, 200, 200CA, 200MC, 210, 220, 220CA, 6690-III, 974, 974D, 3723, 3723CH, 5078, 5078-GA-M, 5078PMAR, 5078CO, 5078TXA, 5078TXB, Type 3 Asphalt, PLS, PRO-PL, PLF 210, Modified AC & Fiber, Asphalt & Fiber, Cold Joint Adhesive, Loop Sealant LW, Loop Sealant P650, PLS, SAMA,

SUPER STRETCH, Pro PL, Sunflex, Membrane #6, Asphalt Cement

Recommended use Pavement Crack and Joint Sealing and Preservation

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer: Crafco, Inc.

Address: 6165 West Detroit St.

Chandler, AZ 85226 USA

Contact Name: Crafco Materials Engineering

Telephone: 602-276-0406 **E-mail:** sales@crafco.com

CHEMTREC: 800-424-9300 (North America)

+ 1-703-527-3887 (International)

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

*Hazards not stated here are "Not classified", "Not applicable" or "Classification not possible".

Label elements

Hazard symbol None.

Signal word Not applicable.

Hazard statement Not applicable.

Precautionary statement

Prevention Not assigned.
Response Not assigned.
Storage Not assigned.
Disposal Not assigned.
Hazard(s) not otherwise None known.

classified (HNOC)

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	30 - 60
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC		64742-52-5	0 - 30
Other components below reportable levels			20

Material name: Deery Hot Applied Sealants
5596 Version #: 06 Revision date: 07-21-2020 Issue date: 01-07-2014

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention, if needed. Call a physician if symptoms develop or persist.

Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Thoroughly wash (or discard) clothing and shoes

before reuse.

Not available.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO

NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and

persists.

Rinse mouth. Do not induce vomiting. Do not use mouth-to-mouth method if victim ingested the **Ingestion**

substance. Call a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed **General information**

In case of ingestion, the decision of whether or not to induce vomiting should be made by the attending physician. Certain pre-existing conditions may make workers particularly susceptible to the effects of this chemical: asthma, allergies, impaired pulmonary function.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Discard any shoes or clothing items that cannot be decontaminated.

5. Fire-fighting measures

Suitable extinguishing media

may cause frothing.

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

Specific methods

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Addition of water or foam to the fire

Do not use a solid water stream as it may scatter and spread fire.

Fire may produce irritating, corrosive and/or toxic gases. Development of hazardous combustion gases or vapours possible in the event of a fire. The following may develop: Acrolein.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear full protective clothing including self contained breathing apparatus. Structural firefighters protective clothing will only provide limited protection.

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA, ALWAYS stay away from tanks engulfed in flame, Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. In the event of fire, cool tanks with water spray. By fire, toxic gases may be formed (COx, NOx). Keep run-off water out of sewers and water sources. Dike for water control.

In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Ventilate closed spaces before entering them. Do not touch or walk through spilled

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Dike far ahead of spill for later disposal. Following product recovery, flush area with water.

Never return spills in original containers for re-use.

Prevent further leakage or spillage if safe to do so. Runoff or release to sewer, waterway or ground **Environmental precautions** is forbidden.

7. Handling and storage

Precautions for safe handling

The product is non-combustible. If heated, irritating vapors may be formed. Do not use in areas without adequate ventilation. Wash hands thoroughly after handling. Wash hands after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. Keep the container tightly closed and dry. Store in a closed container away from incompatible materials. Keep out of the reach of children.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

ComponentsTypeValueFormDISTILLATES
(PETROLEUM),PEL5 mg/m3Mist.

HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)

US. ACGIH Threshold Limit Values

ComponentsTypeValueFormASPHALT (CAS 8052-42-4)TWA0.5 mg/m3Inhalable fume.DISTILLATES
(PETROLEUM),TWA5 mg/m3Inhalable fraction.

HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)

US. NIOSH: Pocket Guide to Chemical Hazards

Form Value Components Type ASPHALT (CAS 8052-42-4) Ceiling 5 mg/m3 Fume. **DISTILLATES** Ceiling 1800 ma/m3 (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) **STEL** 10 mg/m3 Mist. **TWA** 350 mg/m3

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible). Wear chemical goggles; face shield

(if handling molten material).

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear suitable protective clothing and eye/face protection. Use of an impervious apron is

recommended.

Respiratory protection If airborne concentrations are above the applicable exposure limits, use NIOSH approved

respiratory protection.

Thermal hazards During product use, there is a risk of thermal burns.

General hygieneWhen using do not smoke. Avoid contact with eyes. Avoid contact with skin. Keep away from food

considerations and drink. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance Solid.
Physical state Solid.
Form Solid.

Color Black. Dark brown

Odor Product is a black, semi-solid with a burnt tar odor.

Odor threshold Not available. pH Not available.

Melting point/freezing point 150 - 250 °F (65.56 - 121.11 °C) ASTM D36 Softening Point

Material name: Deery Hot Applied Sealants

SDS US

Initial boiling point and

boiling range

> 800 °F (> 426.67 °C)

Flash point

> 400.0 °F (> 204.4 °C)

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

Not available.

(%)

Flammability limit -

upper (%)

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Not available. Vapor pressure Vapor density Not available. **Relative density** Not available.

Solubility(ies)

Solubility (water) Not available. Not available. **Partition coefficient**

(n-octanol/water)

Auto-ignition temperature > 700 °F (> 371.11 °C)

Decomposition temperature Not available. Not available. **Viscosity**

Other information

Density Not Available

Flammability class Combustible IIIB estimated

Percent volatile 0 %

Specific gravity 1.00 - 1.90

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid

Strong oxidizing agents.

Incompatible materials Incompatible with oxidizing agents.

Hazardous decomposition

products

Upon decomposition, product emits acrid dense smoke with carbon dioxide, carbon monoxide, trace

oxides of nitrogen and sulfur, and water.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system.

Skin contact Irritating to skin.

Eye contact Causes eye irritation. Molten material will produce thermal burns.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritation Defats the skin. Causes irritation.

Material name: Deery Hot Applied Sealants

SDS US

5596 Version #: 06 Revision date: 07-21-2020 Issue date: 01-07-2014

Serious eye damage/eye

irritation

Irritating to eyes.

Respiratory or skin sensitization

Respiratory sensitization Not available. **Skin sensitization** Irritating to skin.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityContains no ingredient listed as toxic to reproduction

Specific target organ toxicity

- single exposure

Not available.

Specific target organ toxicity

- repeated exposure

Not available.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. May cause eczema-like skin disorders (dermatitis)

12. Ecological information

EcotoxicityThis product has no known eco-toxicological effects. Not expected to be harmful to aquatic

organisms.

Persistence and degradabilityNot available.Bioaccumulative potentialNot available.Mobility in soilNot available.Other adverse effectsNot available.

13. Disposal considerations

Disposal instructionsDispose of contents/container in accordance with local/regional/national/international regulations.

When this product as supplied is to be discarded as waste, it does not meet the definition of a

RCRA waste under 40 CFR 261.

Hazardous waste code Not applicable.

Waste from residues /

unused products

Dispose of in accordance with local regulations.

Contaminated packaging Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

General information Not regulated as dangerous goods.

Further information If the product is shipped at temperatures below 212°F (100°C), it is not regulated for transport by

ground, air or vessel. If shipped above 212 deg F: "UN3257, Elevated Temperature Liquid, n.o.s.

(Asphalt mixture), 9, PG III"

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 01-07-2014 **Revision date** 07-21-2020

Version # 06

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 0

Flammability: 0 Instability: 0

Material name: Deery Hot Applied Sealants

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

References ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

DisclaimerThe information in the sheet was written based on the best knowledge and experience currently

available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any

other materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Product and Company Identification

Hazard(s) identification: Prevention

Material name: Deery Hot Applied Sealants

5596 Version #: 06 Revision date: 07-21-2020 Issue date: 01-07-2014