Page 1/4

1 Identification of the substance and manufacturer

Trade name:

Product code: Recommended use: Uses advised against: Manufacturer/Supplier:

BLACK STRIPE EXTRA

0000200783 Paint and coatings application. Any that differs from the recommended use. Seymour of Sycamore



phone: 866-399-5562 www.asphaltkingdom.com

2 Hazard(s) identification

Classification of the substance or	mixture
Flammable Aerosols 1	H222 Extremely flammable aerosol.
Gases under Pressure - Liquefied ga	H280 Contains gas under pressure; may explode if heated.
Skin Irritation 2	H315 Causes skin irritation.
Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity - Sing	gle Exposure 3 H335 May cause respiratory irritation.
	eated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.
Additional information:	
GHS Hazard pictograms	
	GHS02 GHS04 GHS07 GHS08
Signal word	Danger
Hazard statements	Extremely flammable aerosol.
	Contains gas under pressure; may explode if heated. Causes skin irritation.
	Suspected of damaging fertility or the unborn child.
	May cause respiratory irritation.
Burne the second state we state	May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces No smoking.
	Do not spray on an open flame or other ignition source.
	Pressurized container: Do not pierce or burn, even after use.
	Do not breathe dust/fume/gas/mist/vapors/spray.
	Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.
	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	Call a poison center/doctor if you feel unwell.
	Specific treatment (see on this label).
	Take off contaminated clothing and wash it before reuse.
	Store in a well-ventilated place. Store locked up.
	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
	Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients Chemical characterization: Mixtures

Chemical D	escription:	This product is a mixture of the substances listed below with nonhazardous additions.	
	components:		
	Calcium Carbonate		≥20-≤25%
64742-89-8	VM&P Naphtha		15-25%
	propane		10-15%
110-54-3	hexane		10-15%
106-97-8	n-butane		5-10%
	Isopropyl Alcohol		1-5%
	PM acetate		1-5%
64742-47-8	Mineral Spirits		1-5%

4 First-aid measures		
After inhalation: After skin contact: After eye contact: After swallowing: Most important symptoms and	Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. Then consult a doctor. Rinse mouth with water. Do not induce vomiting.	
effects:	Dizziness	(Contd. on page 2)

Revised On 01/04/2023

Indication of any immediate medical attention needed: No further relevant information available.	. of page 1)
5 Fire-fighting measures	
Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.	
Special hazards: No further relevant information available. Protective equipment for	
firefighters: A respiratory protective device may be necessary.	
6 Accidental release measures	
Personal precautions, protective	
equipment and emergency procedures: Use respiratory protective device against the effects of fumes/dust/aerosol.	
Methods and material for	
containment and cleaning up: Dispose contaminated material as waste according to section 13.	
7 Handling and storage	
Precautions for safe handling Use only in well ventilated areas.	
Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing co Store locked up.	naitions.
8 Exposure controls/personal protection	
Components with limit values that require monitoring at the workplace: 74-98-6 propane	
PEL (USA) Long-term value: 1800 mg/m ³ , 1000 ppm	
REL (USA) Long-term value: 1800 mg/m ³ , 1000 ppm	
TLV (USA) see Appendix F Minimal oxygen content (D, EX)	
110-54-3 hexane	
PEL (USA) Long-term value: 1800 mg/m ³ , 500 ppm	
REL (USA) Long-term value: 180 mg/m ³ , 50 ppm	
TLV (USA) Long-term value: 50 ppm Skin; BEI	
106-97-8 n-butane	
REL (USA) Long-term value: 1900 mg/m ³ , 800 ppm	
TLV (USA) Short-term value: 1000 ppm (EX)	
67-63-0 Isopropyl Alcohol	
PEL (USA) Long-term value: 980 mg/m ³ , 400 ppm	
REL (USA) Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm	
TLV (USA) Short-term value: 400 ppm	
Long-term value: 200 ppm	
BEI, A4 108-65-6 PM acetate	
WEEL (USA) Long-term value: 50 ppm	
Ingredients with biological limit values:	
110-54-3 hexane	
BEI (USA) 0.5 mg/L	
Medium: urine Time: end of shift	
Parameter: 2.5-Hexanedione without hydrolysis	
67-63-0 Isopropyl Alcohol	
BEI (USA) 40 mg/L Medium: urine	
Time: end of shift at end of workweek	
Parameter: Acetone (background, nonspecific)	
Hygienic protection: Immediately remove all soiled and contaminated clothing. Wash hands after use.	
Avoid contact with the skin.	
Avoid contact with the eyes and skin.	
Breathing equipment: Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open a	arose In
cases where short and/or long term overexposure exists, a charcoal filter respirator should	be worn.
If you suspect overexposure conditions exist, please consult an authority on chemical hyge	ine.
Hand protection: Nitrile gloves. The glove material must be impermeable and resistant to the substance.	
	on page 3)

Revised On 01/04/2023

Page 3/4

Trade name: BLACK STRIPE EXTRA

(Contd.	of page 2)

Eye protection:	(Contd. of page 2)
9 Physical and chemical properties	
Appearance: Odor:	Aerosol. Aromatic
Odor threshold:	Not determined.
pH-value: Melting point/Melting range Boiling point:	Not determined. Undetermined. -44 °C (-47.2 °F)
Flash point: Flammability (solid, gas):	-19 °C (-2.2 °F) Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. 1.2 Vol % 10.9 Vol %
Vapor pressure: Vapor density Evaporation rate Partition coefficient: n-octonal/water	
Solubility: Viscosity: Water:	Not determined. Not determined. 0.0 %
10 Stability and reactivity	
10 Stability and reactivity Reactivity: Conditions to avoid: Chemical stability: Possibility of hazardous reactions: Incompatible materials: Hazardous decomposition:	Stable at normal temperatures. No decomposition if used according to specifications. Not fully evaluated. No dangerous reactions known. No further relevant information available. No dangerous decomposition products known.
11 Toxicological information	
LD/LC50 values that are relevant for	classification:
67-63-0 Isopropyl Alcohol Oral LD50 4,570 mg/kg (rat) Dermal LD50 13,400 mg/kg (rat) Inhalative LC50/4 h 30 mg/l (rat)	
108-65-6 PM acetate Oral LD50 8,500 mg/kg (rat)	
Inhalative LC50/4 h 35.7 mg/l (rat)	
Information on toxicological effects: Skin effects: Eye effects: Sensitization:	No data available. Irritant to skin and mucous membranes. No irritating effect. No sensitizing effects known.
42 Ecological information	
12 Ecological information Aquatic toxicity: Persistence and degradability: Other information: Bioaccumulative potential: Mobility in soil: Remark: Other adverse effects:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents. No further relevant information available. No further relevant information available. Harmful to fish No further relevant information available.
13 Disposal considerations Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. Recommendation: Completely empty cans should be recycled.	

F

Page 4/4

Revised On 01/04/2023

Trade name: BLACK STRIPE EXTRA		
Recommended cleansing agent:	(Contd. of page 3) (Contd. of page 3)	
14 Transport information		
UN-Number DOT DOT ADR Transport hazard class(es): Class Special precautions for user: EMS Number: Packaging Group: UN "Model Regulation":	UN1950 UN1950 Aerosols, flammable 1950 Aerosols 2.1 Gases Warning: Gases F-D,S-U UN 1950 AEROSOLS, 2.1	
15 Regulatory information SARA Section 355 (extremely hazar	dous substances):	
None of the ingredients in this produc	are listed.	
SARA Section 313 (Specific toxic chemical listings): 110-54-3 hexane		
67-63-0 Isopropyl Alcohol		
Toxic Substances Control Act (TSCA): Canadian Domestic Substances Lis (DSL): Consumer Product Safety	All hazardous ingredients are found on the inventory list of substances. It All ingredients are listed or exempted.	
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.	
California Proposition 65 chemicals 1333-86-4 Carbon black	s known to cause cancer:	
100-41-4 ethyl benzene		
Prop 65 chemicals known to cause birth defects or reproductive harm: 110-54-3 hexane		
EPA: 110-54-3 hexane		
16 Other information		
Contact:	Regulatory Affairs	