Asphalt Kingdom

SAFETY DATA SHEET

1. Identification

Product identifier Deery Level & Go and FBJ 6297

Other means of identification None.

Recommended use Pavement Patching and Repair

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer: Crafco, Inc.

Address: 6165 West Detroit St.

Chandler, AZ 85226 USA

Contact Name: Crafco Materials Engineering

Telephone: 602-276-0406 E-mail: sales@crafco.com

CHEMTREC: 800-424-9300 (North America)

+ 1-703-527-3887 (International)

2. Hazard(s) identification

Physical hazards Not classified. **Health hazards** Not classified. **Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

*Hazards not stated here are "Not classified", "Not applicable" or "Classification not possible".

Label elements

Hazard symbol None.

Signal word Not applicable. Hazard Not applicable.

statement

Precautionary statement

Prevention Not applicable. Response Not applicable. Storage Not applicable. **Disposal** Not applicable. None known.

Hazard(s) not otherwise

classified (HNOC)

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
QUARTZ		14808-60-7	0-75
ASPHALT		8052-42-4	10-40
CALCIUM CARBONATE		471-34-1	0-10
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC		64742-52-5	0-10
Other components below repo	rtable levels		26.06

4. First-aid measures

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable

Inhalation for breathing.

Get medical attention, if needed. Call a physician if symptoms develop or

persist.

Skin contact

while

In case of contact, immediately flush skin with plenty of water for at least 15 minutes

removing contaminated clothing and shoes. Thoroughly wash (or discard) clothing and shoes before reuse.

Eye contact

present, DO

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is

NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and persists.

Ingestion ingested the Rinse mouth. Do not induce vomiting. Do not use mouth-to-mouth method if victim

substance. Call a POISON CENTER or doctor/physician if you feel unwell.

Not available. Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed **General information**

In case of ingestion, the decision of whether or not to induce vomiting should be made by the attending physician. Certain pre-existing conditions may make workers particularly susceptible to the effects of this chemical: asthma, allergies, impaired pulmonary function.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Discard any shoes or clothing items that cannot be decontaminated.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Addition of water or foam to the fire

may cause frothing.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from hazardous combustion

Fire may produce irritating, corrosive and/or toxic gases. Development of

the chemical gases or vapours possible in the event of a fire. The following may develop: Acrolein. **Special protective equipment** Firefighters must use standard protective equipment including flame retardant coat,

helmet with

and precautions for

wear full firefighters protective

face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should

protective clothing including self contained breathing apparatus. Structural firefighters

clothing will only provide limited protection.

Fire fighting protective

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard

equipment/instructions

boots, and in

equipment including flame retardant coat, helmet with face shield, gloves, rubber

enclosed spaces, SCBA. ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. In the event of fire, cool tanks with water spray. By fire, toxic gases may be formed (COx, NOx). Keep run-off water out of sewers and water sources. Dike for water control.

Specific methods

tanks with

In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool

water spray. Use water spray to cool unopened containers.

6. Accidental release measures

Personal precautions, clothing during

Keep unnecessary personnel away. Wear appropriate protective equipment and

protective equipment and spilled

clean-up. Ventilate closed spaces before entering them. Do not touch or walk through

emergency procedures

material.

Methods and materials for ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Dike far **containment and cleaning up** ahead of spill for later disposal. Following product recovery, flush area with water.

Never return spills in original containers for re-use.

waterway or ground

Environmental precautions Prevent further leakage or spillage if safe to do so. Runoff or release to sewer,

is forbidden.

7. Handling and storage

Precautions for safe handling The product is non-combustible. If heated, irritating vapors may be formed. Do not use in areas

without adequate ventilation. Wash hands thoroughly after handling. Wash hands after handling.

Observe good industrial hygiene practices.

Conditions for safe storage, Prevent electrostatic charge build-up by using common bonding and grounding

techniques. Store in **including any**

a well-ventilated place. Keep the container tightly closed and dry. Store in a closed

container away incompatibilities

from incompatible materials. Keep out of the reach of children.

SDS US

5449 Version #: 03 Revision date: 02-09-2021 Issue date: 05-01-2015

2 / 7

8. Exposure controls/personal protection

Occupational exposure limits

			-					
116	OCHA	Table	7 1	I imaita	for Air	Contominonto	120	CED
US.	USHA	iable	Z-I	LIMILS	IOF AIF	Contaminants	(29	CFK
							•	

1910.1000) Components	Туре	Value	Form
CALCIUM CARBONATE (CAS 471-34-1)	PEL	5 mg/m3	Respirable fraction
		15 mg/m3	Total dust.
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
QUARTZ (CAS 14808-60-7) US. OSHA Table Z-3 (29 CFR 1910.1000)	PEL	0.05 mg/m3	Respirable dust.
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Valu			
Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.
CALCIUM CARBONATE (CAS 471-34-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	350 mg/m3	
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
ogical limit values No biolo	ogical exposure limits not	ed for the ingredient(s).	

Biological limit values

controls

No biological exposure limits noted for the ingredient(s).

Ensure adequate ventilation, especially in confined areas. Provide adequate ventilation, including

Appropriate engineering

appropriate local extraction, to ensure that the defined occupational exposure limit is

not exceeded.

Individual protection measures, such as personal protective equipment

Wear safety glasses; chemical goggles (if splashing is possible). Wear chemical

goggles; face shield

(if handling molten material).

Skin protection

Eye/face protection

Hand protection

Chemical resistant gloves are recommended. If contact with forearms is likely wear

gauntlet style

gloves.

Wear suitable protective clothing and eye/face protection. Use of an impervious

Other apron is

recommended.

When workers are facing concentrations above the exposure limit they must use Respiratory protection

appropriate

certified respirators.

Material name: Deery Level & Go and FBJ 6297

5449 Version #: 03 Revision date: 02-09-2021 Issue date: 05-01-2015

SDS US **3 / 7**

During product use, there is a risk of thermal burns. **Thermal**

hazards General When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Keep away

hygiene from food

considerations and drink. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance Solid. Physical state Solid. **Form** Solid.

> Color Black, Dark brown

Product is a black, semi-solid with a burnt tar odor. Odor

Odor threshold Not available. На Not available.

Melting point/freezing point 150 - 250 °F (65.56 - 121.11 °C) ASTM D36 Softening Point

Initial boiling point and

boiling range

> 800 °F (> 426.67 °C)

Flash point > 400.0 °F (> 204.4 °C)

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

Not available.

upper (%)

Explosive limit - lower Not available.

Explosive limit - upper Not available.

(%)

4.07 hPa estimated Vapor pressure

Vapor density Not available. **Relative density** Not available.

Solubility(ies)

Solubility (water) Not available. Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature > 700 °F (> 371.11 °C)

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density Not Available

Percent volatile 0 % 1 - 2.2Specific gravity

10. Stability and reactivity

Reactivity Not available.

Chemical stability Material is stable under normal conditions. Possibility of Hazardous polymerization does not occur. hazardous

reactions

Conditions to avoid Strong oxidizing agents.

Incompatible Incompatible with oxidizing agents.

materials Hazardous Upon decomposition, product emits acrid dense smoke with carbon dioxide, carbon

decomposition monoxide, trace

products oxides of nitrogen and sulfur, and water.

11. Toxicological information

Information on likely routes of exposure

May cause irritation to the respiratory

system. Inhalation

Skin contact Irritating to skin.

Eye contact Causes eye irritation. Molten material will produce thermal burns.

May cause discomfort if swallowed. However, ingestion is not likely to be a primary

Ingestion route of

occupational exposure.

Symptoms related to the

physical, chemical and

toxicological characteristics Not available.

Information on toxicological effects

Acute toxicity

Test Results Components Species

CALCIUM CARBONATE (CAS 471-34-1)

Acut е

Oral

LD50 Rat

* Estimates for product may be based on additional component data not

shown.

Skin corrosion/irritation Defats the skin. Causes irritation.

Serious eye damage/eye

irritation

Irritating to eyes.

Respiratory or skin sensitization

Respiratory

sensitization Not available. Irritating to skin. Skin sensitization

No data available to indicate product or any components present at greater than 0.1%

6450 mg/kg

Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY 3 Not classifiable as to carcinogenicity to humans.

NAPHTHENIC (CAS 64742-52-5)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Contains no ingredient listed as toxic to

Specific target organ toxicity - single exposure reproduction Not available.

Specific target organ toxicity

Not available.

- repeated exposure

Aspiration hazard Not available.

Chronic effects

(dermatitis)

Ecotoxicity

Prolonged inhalation may be harmful. May cause eczema-like skin disorders

12. Ecological information

This product has no known eco-toxicological effects. Not expected to be harmful to

aquatic organisms.

Components **Species Test Results**

CALCIUM CARBONATE (CAS 471-34-1)

Aquatic

Western mosquitofish (Gambusia

LC50 Fish affinis) > 56000 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability Not available.

5449 Version #: 03 Revision date: 02-09-2021 Issue date: 05-01-2015

SDS US 5 / 7

Bioaccumulative

potential

Not available.

Mobility in soilNot available.Other adverse effectsNot available.

13. Disposal considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international

regulations. When this product as supplied is to be discarded as waste, it does not

meet the definition of a RCRA waste under 40 CFR 261.

Hazardous waste

code

Not applicable.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated

Offer rinsed packaging material to local recycling facilities.

packaging

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

General information Not regulated as dangerous goods.

Further information If the product is shipped at temperatures below 212°F (100°C), it is not regulated for

transport by ground, air or vessel. If shipped above 212 deg F: "UN3257, Elevated

Temperature Liquid, n.o.s. (Asphalt mixture), 9, PG III"

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ASPHALT (CAS 8052-42-4) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

Classified hazard

Specific target organ toxicity (single or repeated exposure)

categories
SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water

Act Not regulated.

(SDWA)

WARNING: This product contains a chemical known to the State of California to cause

US state regulations cancer.

California Proposition 65

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) QUARTZ (CAS 14808-60-7)

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC) European Inventory of Existing Commercial Chemical	Yes
Europe	Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan United States & Puerto	Taiwan Chemical Substance Inventory (TCSI)	No
Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date	05-01-2015		
Revision date	02-09-2021		

Version # 03

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 0 Flammability: 0 Instability: 0

References ACGIH

EPA: AQUIRE database

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer The information in the sheet was written based on the best knowledge and experience

currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials

or in any process, unless specified in the text.

Revision information Product and Company Identification: Product and Company Identification

Hazard(s) identification: Hazard statement

First-aid measures: Skin contact

Physical & Chemical Properties: Multiple Properties

GHS: Classification

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).