

CRACK FILL MELTER APPLICATORS

RY10MA-PRO

The RY10MA-PRO Professional Crack Fill Melter Applicator's patented design uses up to 50% less fuel than traditional melter applicators and is the industry's only direct-fired style melter applicator with an internal burner. It also features cutting edge innovations, and built-in safety features for a safer operating experience.



SPECIFICATIONS

Fluid Capacity
10 US Gallons

Kettle Steel Thickness
14 Gauge

Empty Weight
142 lbs / 64.5 kg

Max Capacity Weight
240 lbs / 109.0 kg

Fuel Type
Propane

Max Fuel Pressure
5 psi

Burner Type
50,000 BTU/hr Sealed
Burner

Valve Type
1.5" Flow Valve with
Drip Stop

Agitation Type
On-the-fly

PRODUCTIVE

- Melts crack sealant up to 50% faster than torch-fired models and allows you to apply up to 4,800 feet of crack filler per day.
- The patented sealed burner consumes nearly 50% less fuel than traditional torch-fired melter applicators.

RELIABLE

- The enclosed burner design is shielded from the elements and virtually eliminates flame-outs caused by wind, which are common to torch-fired models.
- Two solid front casters allow the operator to maneuver over slanted surfaces with increased stability.

EASY TO OPERATE

- No more wasting time searching for a striker, lighter or matches. Starting a melter has never been easier with our push button electric ignition.
- Side-by-side controls, which include on-the-fly agitation, help the operator control agitation, flow, the application of material, and view and adjust temperature, all without leaving the operating position.

SAFETY BUILT-IN

- Fully equipped with CSA / UL approved regulator and fuel lines provide precise control over fuel flow and kettle temperature.
- The sealed burner is equipped with a CSA / UL approved flame-out sensor which detects flame-outs and prevents fuel from flowing to the burner.