

## CRACK FILL MELTER APPLICATORS

# RY10MA-ELITE



The RY10MA-Elite is the newest and most advanced melter-applier available today. We built upon proven technology from earlier versions of the RY10MA-PRO but added many new features including RynoValve™, RynoDash™, Adjustable Controls as well as dozens of Major General Enhancements.

### SPECIFICATIONS

**Fluid Capacity**  
12.5 US Gallons

**Kettle Steel Thickness**  
14 Gauge

**Empty Weight**  
167.8 lbs / 76.3 kg

**Max Capacity Weight**  
290.3 lbs / 132.0 kg

**Fuel Type**  
Propane

**Max Fuel Pressure**  
5 psi

**Burner Type**  
50,000 BTU/hr  
Sealed Burner

**Valve Type**  
1.25" RynoValve™  
with Drip Stop

**Agitation Type**  
On-the-fly

### INCREASED PRODUCTIVITY

- Melts crack sealant up to 50% faster than torch-fired models — apply up to 4,800 feet of crack filler per day.
- RynoValve™ requires virtually no preheating time and is ready to use as soon as you have hot sealant in the kettle, saving you time between jobs.

### EVEN MORE RELIABLE

- The enclosed burner design is shielded from the elements and virtually eliminates flame-outs caused by wind, which are common to torch-fired models.
- Two solid front casters allow the operator to maneuver over slanted surfaces with increased stability.

### EASIER TO OPERATE

- RynoDash™ allows you to easily ignite and monitor kettle temperatures from the comfort and convenience of the operator position.
- Side-by-side agitation, valve & band controls allow for continuous material agitation while you apply and spread sealant.

### SAFE AND COMFORTABLE

- Fully equipped with CSA / UL approved regulator and fuel lines provide precise control over fuel flow and kettle temperature.
- Handlebars are adjustable from 34" - 42" — optimize valve squeeze distance and spring tensions to reduce operator fatigue.

