



Technical Data

TARGEL™ PLUS

Rubberized Polymer Additive for Pavement Sealers

--- Meets FAA Specification for Pavement Sealer Additives ---

Introduction:

TARGEL™ PLUS is a rubberized polymer additive for use in pavement sealers. TARGEL™ PLUS thickens sealer mixes to suspend sand in the mix and lock the sand in the dried film. TARGEL™ PLUS improves gas and oil resistance and toughens sealer to reduce scuffing and power steering marks. TARGEL™ PLUS helps sealer to dry faster and blacker.

Suggested Formula Rates:

Based on concentrated pavement sealer in the mix, use 1 - 3 gallons of TARGEL™ PLUS per 100 gallons of concentrated pavement sealer. **NOTE: TARGEL™ PLUS must be diluted 1 to 1 with water prior to adding to the mix.**

Additional Formulation Tips:

Based on the starting formulations and job requirements, the best TARGEL™ PLUS formulation is the one that works best for your crew, your equipment, and the weather and pavement conditions.

Generally:

- More TARGEL™ PLUS will result in a thicker, more viscous sealing material.
- More sand will thicken the mixture.
- For optimum pavement sealer performance, do not exceed 8 lbs. of sand per gallon.
- More sealer will thicken the mixture.
- More water will thin the mixture.

Mixing:

With agitator turning, to the predetermined amount of sealer add water (per the sealer manufacturers specification), then add TARGEL™ PLUS (**dilute TARGEL™ PLUS 1 to 1 with water prior to addition.**) Add sand slowly and mix until homogenous.

Application:

Follow pavement preparation procedures, application procedures and recommended number of coats as specified by the sealer manufacturer.

Precautions:

TARGEL™ PLUS modified pavement sealcoating should not be applied when the ambient or pavement temperatures fall below 50° F in a 24 hour period. Do not apply when rain is expected within 24 hours.

Notes:

Keep away from children.
Keep from freezing.
Mix well before using.
Store in airtight container.
Do not store in direct sunlight.
For professional and industrial use only.



ALWAYS READ THE LABEL BEFORE ATTEMPTING TO USE THE PRODUCT: Additional Technical Data Sheets and/or Material Safety Data Sheets (M.S.D.S.) are available upon request.

NOTICE: The methods and techniques described in application specifications represent some that have been used successfully to obtain the desired results. All variations in asphalt, climate conditions and equipment cannot be anticipated by MAINTENANCE INC. The decision to use any of these methods and techniques is entirely at the election and responsibility of the user.

WARRANTY AND DISCLAIMER: There are no express warranties which extend beyond the description on the face hereof. **SELLER DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR ANY PARTICULAR PURPOSE.** Since Seller cannot control the manner or use of its products after their sale, Seller will not be responsible for any consequential or indirect damages. Rather, Seller will, at its option either replace the products sold or refund the purchase price. No warranties will apply if the products are in any way altered or modified after delivery by Seller.